M1.(a)	Multiply volume of propan-1-ol by density								
		Allow measure the mass of the volume added							
		Any reference to concentration of propan-1-ol $CE = 0$	1						
		Divide the mass by the M_r of propan-1-ol	1						
	(b)	Titrate a measured volume of the concentrated HCI added initially to determine moles of HCI used in the experiment							
		Allow addition of AgNO₃ to form AgCl precipitate. Use mass of precipitate to calculate initial moles of HCl added.	1						
		Subtract this number of moles of HCl from the total moles of acid at equilibrium	1						
	(c)	M1 ester will evaporate / escape							
		Allow reactants / products will evaporate	1						
		M2 incorrect values used (to determine K _c)							
		Allow the system will no longer be at equilibrium							
		Do not allow references to equilibrium position shifting alone	1	[6]					
				• •					

M2.(a) Bonds broken = 2(C=O) + 3(H–H) = 2 × 743 + 3 × H–H

Bonds formed =
$$3(C-H) + (C-O) + 3(O-H) = 3 \times 412 + 360 + 3 \times 463$$

Both required

$$-49 = [2 \times 743 + 3 \times (H-H)] - [3 \times 412 + 360 + 3 \times 463]$$

3(H-H) = -49 - 2 × 743 + [3 × 412 + 360 + 3 × 463] = 1450
Both required

1

1

1

1

1

1

(d) 4 mol of gas form 2 mol

At high pressure the position of equilibrium moves to the right to lower the pressure / oppose the high pressure

This increases the yield of methanol

- (e) Impurities (or sulfur compounds) block the active sites Allow catalyst poisoned
- (f) Stage 1: moles of components in the equilibrium mixture Extended response question

1

Stage 2: Partial pressure calculations

Total moles of gas = 2.28

1

1

 p_{co2} = mol fraction × p_{total} = 0.14 × 500 / 2.28 = 30.7 kPa

 p_{H2} = mol fraction × p_{total} = 0.42 × 500 / 2.28 = 92.1 kPa M3 is for partial pressures of both reactants Alternative M3 = pp_{c02} = 0.0614 × 500 pp_{H2} = 0.1842 × 500

 p_{CH3OH} = mol fraction × p_{total} = 0.86 × 500 / 2.28 = 188.6 kPa

 p_{H20} = mol fraction × p_{total} = 0.86 × 500 / 2.28 = 188.6 kPa M4 is for partial pressures of both products Alternative M4 = pp_{CH30H} = 0.3772 × 500 pp_{H20} = 0.3772 × 500

Stage 3: Equilibrium constant calculation $K_{P} = p_{CH3OH} \times p_{H2O} / p_{CO2} \times (p_{H2})^{3}$

1

1

Hence $K_{p} = 188.6 \times 188.6 / 30.7 \times (92.1)^{3} = 1.483 \times 10^{-3} = 1.5 \times 10^{-3}$ Answer must be to 2 significant figures

1

1

Units = <u>kPa</u>⁻²

[16]

M5.D

[1]

[1]

M6.	(a)	(must state correct effect on yield or rate to score the reason mark)						
	Т	effect: higher temp: yield greater or shifts equilibrium to right;	1					
		effect: higher temp: rate increased;	1					
		reason: endothermic						
		OR						
	more particles have E>E _a							
		OR						
		more successful/productive collisions;	1					
	P effect: higher pressure: yield less or shifts equilibrium to left							
	effect: higher pressure: rate increased;							
		reason: increase in gas moles L to R						
		OR						
		greater collision frequency;						
		(Q of L mark)						

(b) M1 equilibrium moles of CO =
$$62.8 - 26.2 = 36.6$$

M2 equilibrium moles of H₂ = $146 - 2(26.2) = 93.6$
M3 total no moles = $36.6 + 93.3 + 26.2 = 156.4$
M4 partial pressure = mole fraction x total pressure

$$K_{p} = \frac{PCH_{3}OH}{PCO \times P^{2}H_{2}}$$

M5

$$\frac{\left(\frac{26.2}{156.4} \times 9.50\right)}{\left(\frac{36.6}{156.4} \times 9.50\right) \times \left(\frac{93.6}{156.4} \times 9.50\right)^2}$$

M6

=

$$\frac{(0.168 \times 9.5)}{(0.234 \times 9.50) \times (0.598 \times 9.5)^2}$$

$$\frac{(1.59)}{(2.22)\times(5.69)^2}$$

1

1

1

1

1

M7 0.022(1) 2.2(I)×10⁻³ 2.2(I)×10⁻¹⁴

M8 MPa⁻² kPa⁻² Pa⁻²

If no subtraction lose M1, M2 and M3) (If ×2 missed in M2, lose both M2 and M3) (If M1 gained but moles of $H_2 = 73.2$ (i.e. double CO), M2 and M3 lost) (If M1 gained but mol $H_2 = 2(146 - 26.2)$, M2 and M3 lost) (If M1 and M2 correct but M3 lost for CE, penalise M6 also) (M4 can be gained from the numbers in the expression for M6 even if these numbers are wrong) (If K_p contains [] lose M5 but then mark on) (If chemically wrong expression for K_p , lose M5, M6 and M7 (allow M8 conseq on their K_p)) (If divided by 9.5, or not used 9.5 at all, lose M6 and M7 (and M4)) (If tried to convert to kPa and is factor(s) of 10 out, penalise

M7.		(a)	(i)	(<i>K</i> _P) = (p _z)²/(p _x)(p _y)³ (penalise use of square brackets, allow ())	1		
		 (ii) X (22–6)/4 = 4 (MPa) (mark is for value 4 only, ignore units) 					
			Y ol	otained by multiplying value for X by 3 (allow conseq on wrong value for X)	1		
			Y 4.	0 × 3 = 12 (MPa) (mark is for value 12 only)	1		
		(iii)	K_{p} :	= 6.0²/4.0 × 12.0³ = 5.21 × 10⁻³ (allow conseq on wrong values for X and			
			(if <i>K</i>	Y e.g. 6²/3 × 9³ = 0.165) ‰ wrong in (a)(i) CE)	1		
			MPa	a ⁻² (allow any unit of P ⁻² provided ties to P used for K, value)	1		
	(b)	higl	h pres	sure expensive (due to energy or plant costs)	1		
		(Ra	te is) s	slow (at lower temperatures)	1		

[8]