

M1.D

[1]

M2.A

[1]

M3.A

[1]

M4.(a) ANY 2 from

- Slow moving neutrons or low (kinetic) energy neutrons

B1

- (They are in) thermal equilibrium with the moderator / Are in thermal equilibrium with other material (at a temperature of about 300 K)

B1

- Have energies of order of 0.025 eV
- Have (range of) KE similar to that of a gas at 300 K or room temperature

2

- (b) (i) Use of $mgh = \frac{1}{2}mv^2$ by substitution or rearranges to make
h the subject
PE for use of equation of motion (constant acceleration)

C1

0.086(1) (m) or 0.086(2) (m)

A1

2

(ii) Correct equation for conservation of momentum

$$m_1u_1 (+ m_2u_2) = m_1v_1 + m_2v_2$$

or states momentum before = momentum after **or**

$$p_{\text{before}} = p_{\text{after}}$$

B1

(Correct clear Manipulation =) $0.065 (+ 0) = - 0.0325 + 0.0975$

or $-0.065 (+ 0) = 0.0325 - 0.0975$ must see signs

Condone non-SI here:

$$65 (+0) = - 32.5 + 97.5$$

B1

States initial kinetic energy = final kinetic energy **or**

States kinetic energy is conserved

Allow equivalent on RHS where masses are summed in one KE term

B1

(Correct clear Manipulation=) $0.04225 = 0.0105625 + 0.0316875$

Or equivalent workings with numbers seen

and $0.04225 = 0.04225 / \text{KE before} = \text{KE after}$

B1

4

(iii) (Percentage / fraction remaining after 1 collision =) $\frac{1}{4} = 25\%$ **seen**

C1

OR

% remaining = $100 \times \frac{1}{2} m(1.3^2 - 0.65^2) / \frac{1}{2} m1.3^2$

or hockey ball = 0.0317 **and** initial ke = 0.04225

or their $\text{KE}_{\text{hb}} / 0.04225$ or their $\text{KE}_{\text{hb}} / \text{their KE}_{\text{T}}$

75(%)

range 75 to 76

A1

2

(iv) **Demonstrates:**

Slowing down / loss of KE of golf ball is like neutrons slowed down / Neutrons can lose KE by elastic collisions also

B1

Differs:

Collisions in a reactor are not always / rarely head-on

or

KE loss is variable

or

Collisions are not always elastic

or

Ratio of mass of neutron to mass of nucleus is usually much smaller in a reactor

B1

2

(v) Water

B1

1

[13]

M5.(a) $m = 16 \text{ g} = 0.016 \text{ kg}$ $r = 0.008 \text{ m}$

Use of $V = \frac{4}{3} \pi r^3$ to give $V = \frac{4}{3} \pi (0.008)^3$

$= 2.1 \times 10^{-6} \text{ m}^3 \checkmark$

The first mark is for calculating the volume

1

Use of density = m / V to give density = $0.016 / 2.1 \times 10^{-6} \checkmark$

The second mark is for substituting into the density equation using the correct units

1

Density = $7.4 \times 10^3 \text{ kg m}^{-3} \checkmark$

The final mark is for the answer.

1

(b) Use of $v^2 = u^2 + 2as$ to give $v^2 = 2 (9.81) (1.27) \checkmark$

(allow use of $mg\Delta h = \frac{1}{2} mv^2$)

$$v^2 = 25 \text{ (24.9)}$$

The first mark is for using the equation

1

$$v = 5.0 \text{ (m s}^{-1}\text{)} \checkmark$$

The second for the final answer

1

(c) Use of $v^2 = u^2 + 2as$ to give $0 = u^2 + 2(-9.81)(0.85) \checkmark$

The first mark is for using the equation

1

$$u^2 = 17 \text{ (16.7)}$$

$$u = 4.1 \text{ m s}^{-1} \checkmark$$

The second for the final answer

1

(d) Change in momentum = $mv + mu = 0.016 \times 5 + 0.016 \times 4.1 \checkmark$

The first mark is for using the equation

1

$$= 0.15 \text{ (0.146) kg m s}^{-1} \checkmark$$

The second for the final answer

1

(e) Use of Force = change in momentum / time taken

$$= 0.15 / 40 \times 10^{-3} \checkmark$$

The first mark is for using the equation

1

= 3.6 N ✓

The second for the final answer

1

- (f) Impact time can be increased if the plinth material is not stiff ✓

Alternative

A softer plinth would decrease the change in momentum of the ball (or reduce the height of rebound) ✓

1

Increased impact time would reduce the force of the impact. ✓

Smaller change in momentum would reduce the force of impact ✓

1

[13]

M6.A

[1]

M7.D

[1]

M8.C

[1]

M9.(a) Max GPE of block = $Mgh = 0.46 \times 9.81 \times 0.63 = 2.84 \text{ J}$ ✓

The first mark is for working out the GPE of the block

1

Initial KE of block = $\frac{1}{2} Mv^2 = 2.84 \text{ J}$

Initial speed of block $v^2 = (2 \times 2.84) / 0.46$

$v = 3.51 \text{ ms}^{-1} \checkmark$

The second mark is for working out the speed of the block initially

1

momentum lost by pellet = momentum gained by block

$= Mv = 0.46 \times 3.51 = 1.61 \text{ kg m s}^{-1} \checkmark$

The third mark is for working out the momentum of the block (and therefore pellet)

1

Speed of pellet = $1.58 / m = 1.58 / 8.8 \times 10^{-3} = 180 \text{ ms}^{-1} (183) \checkmark$

The final mark is for the speed of the pellet

1

At each step the mark is for the method rather than the calculated answer

Allow one consequential error in the final answer

- (b) As pellet rebounds, change in momentum of pellet greater and therefore the change in momentum of the block is greater \checkmark

Ignore any discussion of air resistance

1

Initial speed of block is greater \checkmark

1

(Mass stays the same)

Initial KE of block greater \checkmark

1

Therefore height reached by steel block is greater than with wooden block \checkmark

1

- (c) Calculation of steel method will need to assume that collision is elastic so that change of momentum can be calculated \checkmark

1

This is unlikely due to deformation of bullet, production of sound etc. \checkmark

1

And therefore steel method unlikely to produce accurate results.

